



Rogue Outcast 2X Wash

A lightweight IP65-rated LED wash fixture featuring nineteen pixel-mappable RGBW quad-LEDs, an expansive zoom range, and smooth 16-bit dimming for vibrant color blending and effects.

Perfect for touring, festivals, broadcast, and any indoor or outdoor event requiring a versatile and robust wash light that performs well on camera.

- Powered by nineteen potent 25 W RGBW LEDs for exceptional brightness and color mixing.
- Delivers a versatile zoom range from a narrow 8° to a very wide 66°.
- Offers five individually controlled zones for creating dynamic pixel-mapping effects.
- Built with a durable, lightweight aluminum and magnesium alloy IP65-rated housing.
- Provides a wide 2800 to 10000 K color temperature range with selectable calibrated white.
- Ensures flicker-free on-camera performance with user-selectable Pulse Width Modulation.

SPECIFICATIONS

Optical

Light Source: 19 LEDs (quad-color RGBW) 25 W, (1.5 A), 50,000 hours life expectancy

Color Temperature (range): 2800 to 10000 K

Beam Angle: 8° to 36.1°

Field Angle: 11.8° to 53°

Cutoff Range: 17.5° to 66.1°

Zoom Range: 8° to 66.1°

Lumens – Source: n/a

Lumens – Output: 6,258

Illuminance:

Illuminance (11.8°): 8,713 lux @ 5 m

Illuminance (53°): 694 lux @ 5 m

Selectable PWM: 600Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 270° tilt

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 20 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Curves: 6

Built-in Automated Programs: Yes

Customizable Programs: No

Recall Custom Programs: No

Construction / Physical

Dimensions: 11.92×8.58×14.1" (303x218x361mm)

Weight: 21.2 lb. (9.6 kg)

Exterior Color: Black

Housing Material: Aluminum/magnesium alloy, High-impact flame-retardant polymer

Connections

Power Connection: Bare ended to Seetronic IP65 PowerKon

Power Input: Seetronic IP65 PowerKon

Power Output: Seetronic IP65 PowerKon

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 15, 17, 22, 33, 54, or 56

Modes/Personalities: 8 personalities (15CH, 17CH, 22CH, 33CH, 33CH MS, 54CH, 54CH MS or 56CH)

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V

Power and Current: 291 W, 2.47 A @ 120 V, 60 Hz

Power and Current: 284 W, 1.41 A @ 208 V, 60 Hz

Power and Current: 282 W, 1.28 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, UKCA

IP Rating: IP65 (temporary wet location)

Noise Levels:

Noise Level (Idle): 0.9 dB(A) @ 1 m

Noise Level (Max): 42.6 dB(A) @ 1 m

Noise Level (Full): 44.5 dB(A) @ 1 m

Noise Level (Eco): 27.8 dB(A) @ 1 m

Noise Level (Auto): 27.7 dB(A) @ 1 m

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-07

Seetronic IP65 PowerKon cables

DMX Cables

Flight Case: CP6CASER2W

What's Included

Rogue Outcast R2X Wash IP

Seetronic® powerCON® power cord