

Compact 24U Titan console with touchscreen.

Control 24 universes from a neat, lightweight console. With a built-in touchscreen and more processing power, D3-110 is ready for bigger shows and tighter schedules. Powered by Titan, it supports 24 universes in a compact, self-contained design that fits into any tour, install or rental fleet. Tough, reliable and fully featured, D3-110 delivers high-end control in a neat package.



Control surface.

INTERNAL SCREENS	1x 12.1", 800nit (cd/m²), WXGA capacitive mutli-touch screen with adjustable brightness
EXTERNAL SCREENS	1x optional up to 4K (UHD)
SURFACE LAYOUT	Compact layout (reduced version of D7 & D9 layouts)
PLAYBACK FADERS	10x 60mm faders
FLASH BUTTONS	20x C&K buttons with custom cap
PROGRAMMING / SETUP KEYS	76x backlit Cherry MX Low Profile keys
PLAYBACK PAGING KEYS	3x backlit Cherry MX Low Profile keys
PLAYBACK CONTROL KEYS	5x backlit Cherry MX Low Profile keys, incl. double-width Go key
MACRO/EXECUTOR KEYS	12x backlit Cherry MX Low Profile keys
ATTRIBUTE CONTROL WHEELS	3x high resolution, metal Avo encoders with select buttons
USB WING SUPPORT	1x D3 Wing, T3 Wing, or Titan Mobile Wing
D3 TOUCH SUPPORT	Yes (unlimited)
MOBILE APP	Yes - iOS & Android ("Titan Remote")

Software.

SOFTWARE PLATFORM	Avolites Titan	CONTROL PROTOCOLS	DMX512 (E1.11) Streaming ACN (E1.31) Art-Net & Art-RDM CITP GDTF (through Capture) SMPTE LTC MIDI over USB (MIDI Notes & MTC) Web API
BUILT IN 3D VISUALISATION	Capture Engine		
DMX UNIVERSES PER DEVICE	24 universes (12,288)		
DMX UNIVERSES PER SYSTEM	24 universes (12,288)		
MAX FIXTURES	Unlimited		

TitanNet.

EXPAND PROCESSING	No	MULTI-CONSOLE SESSION	Yes
OFFLOAD PROCESSING	Yes		

Connectivity.

EXTERNAL MONITOR	1x DisplayPort	AUDIO INPUT	1x Neutrik 3-pin XLR
GIGABIT ETHERNET	2x Neutrik etherCON	AUDIO OUTPUT	1x 6.35 mm (1/4") jack
USB 3.2 GEN1	1x USB-C (front) 1x USB-A (rear)	SMPTE LTC INPUT (BALANCED)	1x Neutrik 3-pin XLR (incl. signal indicator)
USB 2.0	2x USB-A (rear)	12V OUTPUT (GOOSENECK)	1x Neutrik 3-pin XLR
DMX (IN & OUT)	4x Neutrik 5-pin XLR	KENSINGTON LOCK	Yes

Physical.

WEIGHT	8.7 kg	DIMENSIONS (W x D x H)	423 x 468 x 202 mm
PACKAGED WEIGHT	TBC	PACKAGED DIMENSIONS	TBC
PACKAGING	Cardboard		

Hardware.

OPERATING VOLTAGE	100-240V AC, 50/60Hz	POWER CONSUMPTION	200W max
CURRENT	3A - 1.5A	HEAT OUTPUT	TBC
POWER CONNECTOR	Neutrik PowerCON TRUE1	IP RATING	IP20 (indoor use only)
POWER SWITCH	Yes	OPERATING TEMPERATURE	0-40°C
SOFT POWER BUTTON	Yes	HUMIDITY	95% non-condensing

Certification and Safety.

CONFORMITY	CE, WEEE, RoHS
------------	----------------

Part Number.

30-02-3110	D3-110 Includes console cover, power cable, recovery stick & 2-year return to base warranty
------------	--

Accessories.

11-02-0123	Desk Lamp Littlite 12" straight
8100-9301	D3-110 Console Cover
09-01-0621	D3-110 Travel Case