




KEY FEATURES

(960) 1.5W RGB LED's in 40 Zones

(400) 5W CW Strobe LED's in 40 Zones

(160) 1.5W RGB StrobeLine LED's in 20 Zones

Completely Fanless Cooling

Integrated L Track for Flexible Mounting

Unique End-to-End Interconnection System

IP65 Rated

Ignite excitement and get the crowd pumping with the new **PULSE BAR L**! The first in an innovative Pulse line of strobe lights, the Pulse Bar is a highly impactful strobe and visual effect bar that injects dynamism and spark into any performance!

Measuring a meter in length, the **PULSE BAR L** incorporates 960 1.5W RGB LEDs distributed across 40 zones along its perimeter. Additionally, it features a central strobe line equipped with 400 5W cool-white LEDs across 40 zones, complemented by 160 1.5W RGB LEDs arranged in 20 zones at its core. When combined, these components deliver an output exceeding 25,191 total lumens.

Infuse your performance with intense, attention-grabbing moments of white or colored light that enhance the energy of the moment. Add impact with rhythmic flashes that synchronize with the music or craft special effects that make for a more visually stimulating experience. Ideal for direct view applications, zone control opens up for a myriad of design possibilities.

The **PULSE BAR L** includes a library of customizable RGB and CW strobe effects along with variable dimming modes and curves for quick programming.

Wrapped in a durable, fully IP65-rated housing, the **PULSE BAR L** is suitable for any environment, indoors or outdoors, and its marine grade coating adds additional protection for harsher environments—even coastal locations.

The fanless convection cooling of the **PULSE BAR L** guarantees silent operation, making it ideal for noise-sensitive environments. Designed for ultimate flexibility, an integrated accessory slot accommodates optional diffusion filters, ND filters and other optics.

The **PULSE BAR L**'s innovative housing allows for end-to-end interconnection and includes integrated L track for flexible mounting and positioning. Trunnions designed for attachment to the L track can be fixed at multiple points to optimize positioning around objects or obstacles.

Controlled via DMX/RDM, the **PULSE BAR L** also features proprietary Aria x2 wireless device management for simplified system setup and maintenance.

When the moment calls for high-impact bursts of light and visually striking effects, look no further. The **PULSE BAR L** delivers!



IP65 Strobe Bar, 1 Meter

SPECIFICATIONS

SOURCE

(1120) 1.5W RGB LEDs
(400) 5W CW Strobe LEDs
50,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

Total Lumen Output
Integrating Sphere
All LED: 22,614 Lumens
CW LED: 25,191 Lumens
RGB LED: 8,434 Lumens
CRI: TBD
Beam Angle: TBD
Field Angle: TBD

EFFECTS

40 Zones of RGB Plate LEDs (20 x 2)
40 Zones of CW Strobe LEDs (20 x 2)
20 Zones of RGB StrobeLine LED's (20 x 1)
1- 20Hz Strobe Rate
Library of Customizable RGB and CW Strobe Effects
Variable Dimming Modes and Curves

COLOR

RGB Color Array

CONTROL / CONNECTIONS

9 DMX Channel Modes (3ch, 11ch, 22ch, 52ch, 92ch, 234ch, 132ch, 242ch, 220ch)
4 Button Control Panel, LED Display
Aria x2 Wireless Device Management
RDM (Remote Device Management)
IP65 5pin XLR DMX In/Out
IP65 Locking Power Cable In

SIZE / WEIGHT

Length: 39.4" (1000mm)
Width: 6.9" (176mm)
Vertical Height: 8.1" (205mm)
Weight: 27.55 lbs (12.5kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
Max Power Consumption: 1300W
5°F to 113°F (-15°C to 45°C)
BTU/hr (+/- 10%) 4433

INCLUDED ITEMS

Safety Cable
IP65 Locking Power Cable
Fixture Interconnect Splice

OPTIONAL ITEMS

BAR L NSP Lens (BLL021)
BAR L WFL Lens (BLL061)
BAR L XFL Lens (BLL101)
BAR L L140 Lens (BLL141)
BAR L L1060 Lens (BLL161)
BAR L Frost (BLL001)
BAR L Dome Frost Lens (BLL181)
BAR L Black Lens (BLL125)
8050000053 - Omega Bracket (Qty.2)
Fixture Interconnect Splice Package (FISP06)
L-Track to M10 Adapter, 70mm (LTR001)
L-Track to M10 Adapter, 44.5mm (LTR008)
L Track C-Clamp & Adapter Assembly, 70mm (LTR100)
L Track C-Clamp & Adapter Assembly, 44.5mm (LTR112)
Interconnect Clamp Adapter (FICA01)

APPROVALS / RATINGS


CE | cETLus | IP65 | FCC | UKCA





IP65 Strobe Bar, 1 Meter

DIMENSIONAL DRAWING



ORDERING INFORMATION



PUL024	1237000344	PULSE BAR L
LTR001	Pending	LTrack A1
LTR008	Pending	LTrack A2
LTR100	Pending	LTrack CA1
LTR112	Pending	LTrack CA2
8050000053	Pending	Omega Bracket

FICA01	Pending	Interconnect Clamp Adapter
BLL201	Pending	Bar L NSP Lens
BLL061	Pending	Bar L WFL Lens
BLL101	Pending	Bar L XFL Lens
BLL141	Pending	Bar L L140 Lens
BLL161	Pending	Bar L L1060 Lens