

**KEY FEATURES**

150W RBL LED Engine

1.5° Beam

125,475 lux @ 5M

True Green Color Filter

FX Package with Rotating & Fixed Gobos, Dual

Stacking Prisms & Frost

Variable CCT 6500K- 16000K

Endless High-Speed 360° Pan and Tilt Movements

NFC & Aria x2 Wireless Device Management

IP65

The **REBEL DARTZ** channels the unapologetic REBEL spirit into a compact, high-impact beam FX mover built for designers who demand speed, precision, and reliability in any environment.

Its fierce 150W RBL engine drives an ultra-narrow 1.5° beam—sharp enough to carve the air and powerful enough to cut through dense atmospherics with ease.

With 360° continuous pan and tilt, **REBEL DARTZ** unleashes unbound motion with kinetic energy. Its dual gobo wheels, layered prisms, and frost equip designers with a deep creative arsenal in a deceptively small footprint.

With an RBL LED engine **REBEL DARTZ** produces a wide, punchy spectrum with smooth output and rich saturation, while a dedicated True Green filter adds even more versatility for building dynamic color-pairings.

As the long-awaited update to the community-favorite DARTZ 360, the **REBEL DARTZ** boasts four times the brightness and more gobos, all in a compact, weather-resistant, IP65-rated design. It rigs fast, travels light, and thrives anywhere the show demands—and with Aria X2 wireless DMX and RDM, NFC configuration, and five selectable fan modes, including a silent setting, it keeps setup, service, and noise control firmly dialed in.

Built to hit harder, shine sharper, and leave a mark that makes every design unmistakably REBEL, the **REBEL DARTZ** is a fixture that refuses to blend in.



150W RBL Beam FX Fixture

SPECIFICATIONS

SOURCE

150W RBL LED Engine
20,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

Total Lumen Output:
1,785 (Integrating Sphere)
TBA (Goniometer)
125,475 lux @ 5M
Beam Angle 1.5°

EFFECTS

Variable Strobe Rate: 1- 20Hz
Remote Focus
Heavy Frost Filter
Dual Independent Stacking Prisms (6 Facet Linear & 8 Facet Circular)
Variable 16-bit Dim Curve Modes
DMX Controllable LED Refresh Rate
Pan Angle: 360/540°
Tilt Angle: 360/270°
Continuous 360° Pan and Tilt Rotation

COLOR

RBL Color Array
True Green Color Filter
Variable CCT 3200K- 16000K
Virtual Gel Swatch Book

GOBOS

2 Gobo Wheels
10 Interchangeable-Rotating / Indexing Metal Gobos
16 Static-Stamped Metal Gobos

CONTROL / CONNECTIONS

2 DMX Channel Modes
(4) Button Touch Panel
180° Reversible LCD Menu Display
Hibernation Mode (Power Save)
DMX, RDM, Art-Net and sACN Protocol Support
Aria x2 Wireless Device Management
NFC Configuration
IP65 5pin DMX In/Out
IP65 RJ45 Ethernet In/Out
IP65 Locking Power In/Out

SIZE / WEIGHT

Length: 13.3" (337mm)
Width: 8.6" (219mm)
Height: 18.8" (478mm)
Weight: 35 lbs. (15.9kg)

ELECTRICAL / THERMAL

AC 100-240V 50/60Hz
240W Max Power Consumption
Power Thru Capacity: 10A (4 units @115V, 9 units @240V)
-4°F to 113°F (-20°C to 45°C)

INCLUDED ITEMS

Omega Bracket x2
Safety Cable
Power Cable

APPROVALS / RATINGS

CE | cETLus | IP65 | FCC




ORDERING INFORMATION

US SKU	EU SKU	DESCRIPTION
REB224	PENDING	Elation Rebel Dartz







ROTATING GOBOS




FIXED GOBOS



PRISMS



COLORS



True
Green

