



Rogue Outcast 3X Wash

An IP65-rated LED wash fixture featuring a fast zoom, nine pixel-mappable zones, and 37 powerful RGBW LEDs that deliver excellent color blending and a strong output. Perfect for a wide range of applications from touring and outdoor festivals to on-camera use, especially in environments demanding durability against the elements.

- Generates a powerful, even field of light from thirty-seven 25 W RGBW LEDs.
- Offers a versatile zoom range from a tight 9.3° beam to an expansive 62.6° wash.
- Built with a rugged yet lightweight aluminum and magnesium alloy IP65-rated housing.
- Ensures flicker-free on-camera operation with selectable PWM and a calibrated white setting.
- Achieves exceptionally smooth fades with 16-bit dimming and six distinct dimming modes.
- Provides flexible programming with four DMX personalities and RDM for remote setup.

SPECIFICATIONS

Optical

Light Source: 37 LEDs (quad-color RGBW) 25 W, (1.5 A), 50,000 hours life expectancy

Color Temperature (range): 2800 to 10000 K

Beam Angle: 9.3° to 33.9°

Field Angle: 11.6° to 49.5°

Cutoff angle: 13.1° to 62.6°

Zoom Angle: 9.3° to 62.6°

Lumens – Source: 17,000

Lumens – Output: 13,440

Illuminance:

Illuminance (9.3°): 18,260 lux @ 5 m

Illuminance (62.6°): 1,556 lux @ 5 m

Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 6,000 Hz, 15,000 Hz

Dynamic Effects

Pan and Tilt: 540°/270°

Pan and Tilt Ranges: 180°, 360°, 540° Pan/90°, 180°, 230° Tilt.

Dimmer: Electronic

Shutter/Strobe: Electronic

Zoom: Motorized

Strobe Rate: 0 to 25 Hz

Standalone Color Mixing: Yes

Color Temperature Presets: Yes

Dim Curves: 4

Built-in Automated Programs: Yes

Customizable Programs: No

Recall Custom Programs: No

Construction / Physical

Dimensions: 15.59 x 11.73 x 17.20 in (396 x 298 x 437 mm)

Dimensions (shipping size): 23.62x 14.17 x 18.70 in (600 x 360 x 475)

Weight: 38.2 lb. (17.38kg)

Exterior Color: Black

Housing Material: High-impact flame-retardant polymer.

Connections

Power Connection: Edison (local) plug to Seetronic PowerKON IP65

Power Input: Seetronic PowerKON IP65

Power Output: Seetronic PowerKON IP65

Data Connectors: 5-pin XLR

Cable Length (power): 5 ft (1.5 m)

Control

Control Protocol: DMX, RDM

DMX Channels: 21, 62, 71, 107

Modes/Personalities: 4 personalities

Electrical

Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)

Power Linking: 2 units @ 120 V; 3 units @ 208 V; 3 units @ 230 V

Power and Current: 711 W, 5.98 A @ 120 V, 60 Hz

Power and Current: 701 W, 3.40 A @ 208 V, 60 Hz

Power and Current: 695 W, 3.07 A @ 230 V, 50 Hz

Certifications / Qualifications

Certifications: CE, MET, FCC, FCC, UKCA

IP Rating: IP65, temporary outdoor/wet use

Noise Levels:

Noise Level (Idle): 22.8 dB(A) @ 1 m

Noise Level (Auto): 47.5 dB(A) @ 1 m

Noise Level (Eco): 34.3 dB(A) @ 1 m

Noise Level (Full): 47.3 dB(A) @ 1 m

Noise Level (Max): 37.2 dB(A) @ 1 m

Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

Optional Accessories

Professional Clamps: CTC-50HC, CTC-50HCN

Safety Cable: SC-08

Seetronic IP65 PowerKon cables

DMX Cables

UPLOAD 08 software uploader

What's Included

Rogue Outcast 3X Wash

Seetronic PowerKon IP65 power cord

(2) 140D Omega brackets with mounting hardware